

Strut Cushion Clamp

8500

SIZES: 1/4" OD through 4 1/8" OD

MATERIAL: Electro-galvanized steel with thermoplastic insulating liner.

ALSO AVAILABLE IN: Stainless Steel (304 SS) and Stainless Steel (316 SS)

SERVICE: Prevents shock, vibration, corrosion, and metal contact in strut fastening applications.



| PART No. | Copper Tube | IPS | Weight Each (LBS) | Pkg. Qty. |
|-----------------------|-------------|--------|-------------------|-----------|
| 8500 - 1/4OD | | | 0.11 | 25 |
| 8500 - 3/8OD | 1/4" | | 0.11 | 25 |
| 8500 - 1/2OD | 3/8" | | 0.11 | 25 |
| 8500 - 5/8OD | 1/2" | | 0.12 | 25 |
| 8500 - 3/4OD | 5/8" | | 0.13 | 25 |
| 8500 - 7/8OD | 3/4" | 1/2" | 0.20 | 25 |
| 8500 - 1OD | | | 0.21 | 25 |
| 8500 - 1 1/8OD | 1" | 3/4" | 0.27 | 25 |
| 8500 - 1 1/4OD | | | 0.29 | 10 |
| 8500 - 1 3/8OD | 1 1/4" | 1" | 0.31 | 10 |
| 8500 - 1 1/2OD | | | 0.35 | 10 |
| 8500 - 1 5/8OD | 1 1/2" | 1 1/4" | 0.40 | 10 |
| 8500 - 1 7/8OD | | 1 1/2" | 0.42 | 10 |
| 8500 - 2OD | | | 0.46 | 10 |
| 8500 - 2 1/8OD | 2" | | 0.49 | 10 |
| 8500 - 2 3/8OD | | 2" | 0.60 | 10 |
| 8500 - 2 5/8OD | 2 1/2" | | 0.62 | 10 |
| 8500 - 3 1/8OD | 3" | | 0.65 | 10 |
| 8500 - 4 1/8OD | 4" | | 0.90 | 10 |